

REFRACTORY PANELS



TIME IS MONEY- Cut down on time and inventory with Hargrove's CUT-TO-FIT replacement panels



- **ENGINEERED FOR EXTREME HEAT WITH EXCELLENT THERMAL PROPERTIES**
- **MEETS ASTM C133 REQUIREMENTS**
- **WITHSTANDS TEMPERATURES OVER 1900F**
- **MINIMAL THERMAL EXPANSION**
- **STEEL AND FIBER REINFORCEMENT**
- **CAN BE USED AS A LEFT, RIGHT, BACK OR FLOOR PANEL**
- **AVAILABLE IN 2 SIZES (24" X 28" & 24" X 40")**
- **24" X 28" HAS A TAPERED EDGE FOR A FINISHED LOOK WHEN USED AS A LEFT OR RIGHT PANEL**
- **24" X 28" CAN BE SHIPPED VIA UPS WITH OUR SPECIAL PACKAGING**
- **24" X 40" IS TAPERED ON 2 SIDES**

CUT-TO-FIT panels can be installed in prefabricated, factory built, zero clearance and masonry fireplaces. All panels are 3/4" thick and can replace any panel 3/4" or smaller. Panels may be cut many ways but we suggest a wet-saw or a saw with a masonry blade. A "burn in" period is also required, which limits the first few times the fireplace is used after the installation of the panels.

CUT-TO-FIT REFRACTORY PANEL	
MAXIMUM TEMPERATURE	
	1040 C
	1900 F
COMPRESSIVE STRENGTH	
	50 MPa
	7100 psi
MODULUS OF RUPTURE	
	8 MPa
	1160 psi

HARGROVE MANUFACTURING CORPORATION
 207 WELLSTON PARK ROAD - SAND SPRINGS OK 74063
 800.725.4166
www.hargrovegaslogs.com