

TECHNICAL S	PECIFICATIONS	
VOLTS	120V / 240V	
AMPS	12. 5A / 12. 1A	
WATTS	1500W / 3000W	
HIGH HEATER	1500W / 3000W watts	
LOW	750W /1500W watts	
NO HEATER	57.1 WATTS MAX	
QUANTITY	218PCS LED	
LAMPS WATTS	0. 5W&O. 15W&O. 06W	
TOTAL WATTS	43. 3W	
ROTOR MOTOR	3 at 8.7 watts	
HEIGHT. WIDTH. DEPTH	66 1/8 " X 29 3/8 " X 15 "	
GLASS VIEWING OPENING	65 " X 20 "	
SURROUND SIZE	65 1/4 " X 29 5/8 " X 13 1/4 "	
SHIPPING SIZE	71 5/8 " X 18 7/8 " X 34 5/8 "	
SHIPPING WEIGHT	211. 2 LBS	
UNIT	1	
GLASS FRONT	Included	
PLUG LOCATION	Left Side	
CORO LENGTH	70.9 < L < 95.5	
APPROX. HEATING AREA	400 SQ FT / 800 SQ FT	



SERIES TRU VIEW	MODEL TRY OF RESPONE		REV
IKO VIEW	TRV-65 BESPOKE		1
SCALE 1" =1' -0"	DATE: 11/26/2022	SHEET 1 OF 1	